

EAC-SP 1-Phase AC Power Sources

250 – 12.000 VA



(19" x 3 U x 620 mm)

OVERVIEW

- Simulation of single-phase networks
- AC and DC operation
- 250 – 12.000 VA power output
- 0 – 700 V AC / 1.000 V DC output voltage per phase
- 1 – 2.000 Hz variable frequency (sine, square, triangle)
- Currents up to 600 A per phase
- Graphical display
- Measuring of: voltage, current, average and peak current, effective power, idle power, apparent power, power factor, crest factor
- Constant voltage and constant current modes
- Free memory space to store user programmed curves via optional SD card slot
- External oscillator input ±10 V with adjustable time delay up to 70 ms
- Digital interface IEEE, RS-232/485, USB, LAN

- Galvanically isolated 0 – 5 V or 0 – 10 V analogue interface
- Script control: process programming and booting from memory card
- Creation of user defined waveforms and programming via memory card or digital interface
- Data logging function: output values can be saved at adjustable time intervals to a memory card
- Script operation in combination with data logging function provides and stand-alone testing
- Sync input synchronizes the device with external sources
- Sync output triggers external measurement instruments or similar
- ‘Brown-out’ simulation where output voltage drops for a determined amount of half periods
- Output voltage for a determined amount of time
- Special versions available on request

PRODUCT EXAMPLES

Type	Power VA	Voltage V AC / V DC	Effective Current A	Dimensions
EAC/SP 250	250	0 – 300 / 0 – 425	0 – 3	19" x 3U x 620 mm
EAC/SP 500	500	0 – 300 / 0 – 425	0 – 6	19" x 3U x 620 mm
EAC/SP 1500	1.500	0 – 300 / 0 – 425	0 – 10	19" x 3U x 620 mm
EAC/SP 2000	2.000	0 – 300 / 0 – 425	0 – 16	19" x 6U x 620 mm
EAC/SP 3000	3.000	0 – 300 / 0 – 425	0 – 20	19" x 6U x 620 mm
EAC/SP 4500	4.500	0 – 300 / 0 – 425	0 – 30	19" x 9U x 620 mm
EAC/SP 5000	5.000	0 – 300 / 0 – 425	0 – 35	19" x 9U x 620 mm
EAC/SP 6000	6.000	0 – 300 / 0 – 425	0 – 40	19" x 9U x 620 mm
EAC/SP 7500	7.500	0 – 300 / 0 – 425	0 – 50	19" x 9U x 620 mm
EAC/SP 8000	8.000	0 – 300 / 0 – 425	0 – 60	19" x 12U x 620 mm
EAC/SP 9000	9.000	0 – 300 / 0 – 425	0 – 70	19" x 12U x 620 mm
EAC/SP 10500	10.500	0 – 300 / 0 – 425	0 – 80	19" x 12U x 620 mm
EAC/SP 12000	12.000	0 – 300 / 0 – 425	0 – 90	19" x 18U x 620 mm

OPTIONS

Appendix	Description
./230	Input 230 / 207 – 253 V AC
./400	Input 400 / 360 – 440 V AC
./3P208	Input 3 x 208 / 187 – 229 V AC
./3P400	Input 3 x 400 / 360 – 440 V AC
./3P480	Input 3 x 480 / 432 – 528 V AC
./V500	Extended voltage range 0 – 500 V AC / 0 – 700 V DC -40
% Imax	
./V700	Extended voltage range 0 – 700 V AC / 0 – 1.000 V DC -
50 % Imax	
./F1000	Extended frequency range 1 – 1.000 Hz
./F2000	Extended frequency range 1 – 2.000 Hz
./LT	Interface IEEE 488
./LTRS485	Interface RS-485
./LTRS232	Interface RS-232
./LAN	Interface LAN
./USB	Interface USB
./ATI 5	Galvanically isolated analogue interface 0 – 5 V
./ATI 10	Galvanically isolated analogue interface 0 – 10 V
./EXT/OSZ	OSZ external oscillator input
./SD	SD card slot
./SYNC A	Sync output for triggering external measurement devices or similar (optional)
./SYNC E	Sync input for synchronization with external sources (optional)
./INTLOCK	Interlock input / safety shutdown
./DIP	Disengageable output voltage during a specific number of half periods
./GATE	Engageable output voltage during a specific amount of time (digital interface required)
./APuls	Adjustable puls sequence (digital interface required)
./LoadR	Load reverse energy recovery
./LoadLR	Load energy recovery / regeneration in development

TECHNICAL DATA

Input Voltage Specification

Input voltage range	230 V AC / 400 V AC / 3 x 208 V AC / 3 x 400 V AC / 3 x 480 V AC ±10 %
Input frequency	47 – 63 Hz

Output Specification

Grid regulation	0,10 %
Load control	0,10 %
Distortion Pmax	0,15 %
Programming accuracy	100 mV
AC voltage	
Programming accuracy	100 mV
DC voltage	
Programming accuracy < 10 A	1 mA
Effective constant current > =10 A	10 mA
Programming accuracy	0,1°
Activation phase	
Programming accuracy	0,1 Hz
Frequency	
Frequency standard	0 – 500 Hz
External oscillator input	0 – 10 V / 1 kHz
Resolution, Measurement,	100 mV
Effective voltage,	
DC voltage,	
Peak voltage	
Resolution, Measurement <10 A	1 mA
Effective current, DC current	
Peak current > =10 A	10 mA
Resolution, Measurement < 10 A	10 mW
Active power > =10 A	100 mW

Programming & Control

Output Control and	Front panel and/or optional Analog 0 - +5V/+10V isolated/
Monitoring	Digital 12 bit: RS-232, RS-485, IEEE488, LAN, USB, SD card

Ambient Conditions

Cooling	Fans
Operating temperature	0 – 50°C
Storage temperature	-20 – 70°C
Humidity	< 80 %
Operating height	< 2.000 m
Weight	30 – 150 kg



riešenia na presné meranie

Elso Philips Service
 Jilemnického 2; 911 01 Trenčín
 tel: +421 32 6582410
 fax: +421 32 6582592
 email: elso@elso.sk
 web: www.elso.sk